



Expansion Enclosure / JBOD

Versatile capacity expansion and convenient storage scalability

Infotrend EonStor GS/GSe and EonStor DS systems offer easy scalability on demand, allowing you to increase storage capacity when needed. The JB 3000 series of expansion enclosures (JBODs) are available in multiple form factors, from 2U 12-bay to 4U 90-bay. Their flexibility means they are an excellent choice for diverse environments, budgets, and capacity needs.

JB 3000 models are offered in single or high availability dual controller configurations and ship with redundant 80 PLUS power supplies by default. For additional energy savings, they employ smart drive spin-down while maintenance is easy with modular hardware. Assured Infotrend reliability is backed by a 3-year warranty.

PHYSICAL SPECIFICATIONS

Product Series		JB 3000						
Form Factor		2U 24-bay	2U 25-bay	2U 12-bay	3U 16-bay	4U 60-bay	4U 90-bay	
Model		JB 3024 RB/SB JB 3024 RBA/SBA	JB 3025 RBA/SBA	JB 3012 R/S JB 3012 RA/SA	JB 3016 R/S JB 3016 RA/SA	JB 3060 RL/GL	JB 3090 R/G	
		Note: G: Single controller, not upgradable R: Dual redundant controllers S: Single upgradable to dual redundant controllers B: 2.5" drive A: GS type tray L: One drawer						
Onboard SAS Expansion Ports		2	3	2	2	3	4	
Supported Drives		• 2.5" SAS SSD • 2.5" 12Gb/s SAS 10,000 RPM RPM HDD			• 3.5" 12Gb/s NL-SAS 7,200 RPM HDD • 2.5" SATA SSD			
		Note: For the latest compatibility details, refer to our official website for the latest Compatibility Guide.						
Dimensions (Without Chassis Ears and Protrusions) (W x H x D)		449 x 88 x 500 mm	449 x 88 x 500 mm	449 x 88 x 500 mm	449 x 130 x 500 mm	448 x 176 x 840 mm	435 x 175.8 x 965.6 mm	
Package Dimensions (W x H x D)		780 x 338 x 588 mm	780 x 338 x 588 mm	780 x 379 x 588 mm	780 x 423 x 588 mm	620 x 460 x 1140 mm	620 x 465 x 1250 mm	
Power Supply Unit	Power Supplies (Redundant and Hot-swappable)	Global	460W x 2 (80 PLUS Bronze)	460W x 2 (80 PLUS Bronze)	• JB 3012 RA/SA , JB 3016 RA/SA : 460W x 2 (80 PLUS Bronze) • JB 3012 R/S , JB 3016 R/S : 530W x 2 (80 PLUS Bronze)		1200W x 2 (80 PLUS Platinum)	1300W x 2 (80 PLUS Platinum)
		EU	800W x 2 (80 PLUS Bronze)				1300W x 2 (80 PLUS Platinum)	
	AC Voltage	Global	100-240VAC @10-5A				100-127VAC@12.47A, 200-240VAC @7.08A	100-127VAC @12A, 200-240VAC @8.5A
		EU	100-127VAC @10A, 200-240VAC @5A				100-127VAC @12A, 200-240VAC @8.5A	
	Frequency		50-60 Hz					
Safety Standards		• Electromagnetic compatibility: CE, BSMI, FCC • Safety: UL, BSMI, CB						

WARRANTY AND SERVICE

Service and Support	Standard Service	3-year limited hardware warranty and 8 x 5 phone, web, and email support (batteries are covered under warranty for 2 years)
	Upgrade or Extension Options	Warranty extension: Can extended standard service up to 5 years The following Service can be upgraded to 5 years <ul style="list-style-type: none"> • Upgrade: Replacement part dispatch on the next business day • Advanced service: phone, web, and email support + onsite diagnostics on the next business day • Premium service: phone, web, and email support + onsite diagnostics in 4 hours
		Note: Options may vary by region. For more details, please contact our sales representatives.
	Technical Support	Get information on system installation and maintenance, download technical documents and software, or issue a support ticket
Product Services		Register products, download firmware, apply for licensing services, create product repair tickets, or check product repair status

Asia Pacific (Taipei, Taiwan)
Infotrend Technology, Inc.
Tel : +886-2-2226-0126
E-mail : sales.ap@infotrend.com

China (Beijing, China)
Infotrend Technology, Ltd.
Tel : +86-10-6310-6168
E-mail : sales.cn@infotrend.com

Japan (Tokyo, Japan)
Infotrend Japan, Inc.
Tel : +81-3-5730-6551
E-mail : sales.jp@infotrend.com

Americas (Sunnyvale, CA, USA)
Infotrend Corporation
Tel : +1-408-988-5088
E-mail : sales.us@infotrend.com

EMEA (Basingstoke, UK)
Infotrend Europe Ltd.
Tel : +44(0)-1256-305-220
E-mail : sales.eu@infotrend.com



Visit Our Website